

SIR[®] 30 ADVANCED PRODUCT SPECIFICATIONS

System																																					
Antenna Support	Compatible with most GSSI antennas																																				
Number of Channels	Records data from 1 to 4 hardware channels simultaneously; two 4 channel systems can be connected to form an 8 channel system																																				
Data Storage	Internal memory: 4 channel 500 GB Internal SSD, 2 channel 250 GB Internal SSD GPS data logged internally																																				
Display Modes	Linescan and O-scope. In Linescan display, 256 color bins are used to represent the amplitude and polarity of the signal																																				
Operational Modes	External laptop, standalone with external monitor and keyboard or remote command set																																				
Data Acquisition																																					
Data Format	RADAN (.dzt)																																				
Scan Rate Examples	Output Data Resolution: 32-bit <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th colspan="2">1-4 Channels @ 100 KHz PRF</th> <th colspan="2">1-4 Channels @ 800 KHz PRF</th> </tr> <tr> <th>Samples</th> <th>Max Rate (scans/Sec)</th> <th>Samples</th> <th>Max Rate (scans/Sec)</th> </tr> </thead> <tbody> <tr> <td>256</td> <td>326</td> <td>256</td> <td>1449</td> </tr> <tr> <td>512</td> <td>178</td> <td>512</td> <td>990</td> </tr> <tr> <td>1024</td> <td>93</td> <td>1024</td> <td>606</td> </tr> <tr> <td>2048</td> <td>48</td> <td>2048</td> <td>341</td> </tr> <tr> <td>4096</td> <td>24</td> <td>4096</td> <td>182</td> </tr> <tr> <td>8192</td> <td>12</td> <td>8192</td> <td>94</td> </tr> <tr> <td>16,384</td> <td>8</td> <td>16,384</td> <td>48</td> </tr> </tbody> </table>	1-4 Channels @ 100 KHz PRF		1-4 Channels @ 800 KHz PRF		Samples	Max Rate (scans/Sec)	Samples	Max Rate (scans/Sec)	256	326	256	1449	512	178	512	990	1024	93	1024	606	2048	48	2048	341	4096	24	4096	182	8192	12	8192	94	16,384	8	16,384	48
1-4 Channels @ 100 KHz PRF		1-4 Channels @ 800 KHz PRF																																			
Samples	Max Rate (scans/Sec)	Samples	Max Rate (scans/Sec)																																		
256	326	256	1449																																		
512	178	512	990																																		
1024	93	1024	606																																		
2048	48	2048	341																																		
4096	24	4096	182																																		
8192	12	8192	94																																		
16,384	8	16,384	48																																		
Scan Interval	User-selectable																																				
Number of Samples per Scan	256, 512, 1024, 2048, 4096, 8192, 16,384																																				
Operating Modes	Continuous (time), Survey Wheel (distance triggered) or Point Mode (with static stacking up to 100,000 scans)																																				
Time Range	0-25,000 nanoseconds full scale, user-selectable Gain: manual adjustment from -42 to +126 dB. Number of segments in gain curve is user-selectable from 1 to 8																																				
Standard Real-Time Filters	Infinite Impulse Response (IIR) - Low and High Pass, vertical and horizontal Finite Impulse Response (FIR) - Low and High Pass, vertical and horizontal																																				
Advanced Real-Time Filters	Migration, Surface Position Tracking, Signal Floor Tracking, Adaptive Background Removal																																				
External Marker	Three different inputs/codes: Antenna, Back panel, Accessory connector																																				
Automatic System Setups	Storage of an unlimited number of system setup files for different survey conditions and/or antenna deployment configurations																																				
Automatic Antenna Recognition	Automatic recognition of Smart Antennas to allow maximum compliant transmit rate																																				
Languages																																					
	English																																				
Operating																																					
Operating Temperature	-10°C to 50°C external (14°F to 122°F)																																				
Battery	260W max (120W typical) at 95-250VAC 50/60Hz or +10VDC to +28VDC																																				
Transmit Rate	Up to 800 KHz (International), US/Canada and CE rates depend on antenna model																																				
Input/Output																																					
Available Ports	Antenna inputs (2 or 4), Survey wheel, Marker, DC power input, Serial RS232 (GPS port), Sync connector, Accessory connector, HDMI video, Ethernet (2), USB (3)																																				

Geophysical Survey Systems, Inc.

40 Simon Street • Nashua, NH 03060-3075 USA • www.geophysical.com

