## To Whom it May Concern:

This is to certify that electromagnetic radiation emissions from transducers (antenna with transmitting and receiving electronics) manufactured by Geophysical Survey Systems, Inc. (GSSI) DO NOT constitute a safety or health hazard to operating personnel.

Emissions from GSSI transducers are far below the 10mW/cm<sup>2</sup> (100W/m<sup>2</sup>) level specified by the United States Occupational Safety and Health Administration (OSHA) regulations

## Paragraph 1910.97 states:

"For normal environmental conditions and for incident electromagnetic frequencies from 100 MHz to 100 GHz, the radiation protection guide is 10 mW/cm<sup>2</sup> (milliwatt per square centimeter) as averaged over any possible 0.1 hour period."

The following is the average power density data at 5cm and wide band using GSSI GPR products.

ANTENNA (MHz)	AVERAGE POWER DENSITY (mW/cm² @ 5 cm)	OSHA SPEC. (mW/cm²)
100	Less than 0.015	10
200	Less than 0.002	10
270	Less than 0.001	10
300/800	Less than 0.0002	10
350	Less than 0.0002	10
400	Less than 0.0002	10
500	Less than 0.00001	10
900	Less than 0.00001	10
1000	Less than 0.00001	10
1500	Less than 0.00001	10
1600	Less than 0.00002	10
2000	Less than 0.0006	10
2300	Less than 0.00002	10
2600	Less than 0.0015	10
2700	Less than 1.0	10
Terravision	Less than 0.00001	10
FlexNX	Less than 0.0032	10
NX25	Less than 0.0032	10

## GEOPHYSICAL SURVEY SYSTEMS, INC.

Jay Desruisseaux Quality Manager 10/13/2023 Y-15-219 Rev C

